



# Savin 2560/2575

## COPIER SPECIFICATIONS

<b>Configuration</b>	Console
<b>Printing Process</b>	Four laser beam scanning and electro-photographic printing
<b>Copy Resolution</b>	1200 dpi
<b>Gray Scale</b>	Scanning: 256 levels
<b>Standard Memory Capacity</b>	RAM 128 MB/40 GB HDD
<b>Document Server</b>	Storage up to 10,000 pages
<b>Continuous Copy Speed</b>	60/75 cpm (8.5" x 11")
<b>Copy Size</b>	5.5" x 8.5" - 11" x 17"
<b>First Copy</b>	Less than 3.5 seconds
<b>Originals</b>	Sheet/Book/3 dimensional
<b>Max. Original Size</b>	11" x 17"
<b>Min. Original Size</b>	5.5" x 8.5"
<b>Warm-up Time</b>	Less than 300 seconds from off mode 25 seconds from low power mode
<b>Multiple Copying</b>	Up to 999
<b>Auto Duplex</b>	Unlimited
<b>Standard Paper Capacity</b>	1,550 x 2 Tandem Tray + 550 x 2 Trays + 100 sheet Bypass
<b>Optional Paper Capacity</b>	4,000 sheet LCT (total capacity 8,300)
<b>Output Tray Capacity</b>	
500 sheets	8.5" x 11"/8.5" x 14"
250 sheets	All other sizes
<b>Zoom Range</b>	25% to 400% in 1% steps
<b>Enlargement</b>	121%, 129%, 155%, 200%, 400%
<b>Reduction</b>	93%, 85%, 78%, 73%, 65%, 50%
<b>Copy Paper Weight</b>	14 - 34 lb. Bond (Std. Trays) 14 - 43 lb. Bond/110 lb. Index (Bypass Feed) 17 - 34 lb. Bond (Duplex)
<b>Dimensions (WxDxH)</b>	28" x 30" x 47" (includes ARDF)
<b>Weight</b>	Less than 200 Kg
<b>Power Source</b>	120V, 60Hz, 20A

## STANDARD ACCESSORIES

<b>Document Feeder</b>	Standard duplex one pass
<b>Scanning</b>	Standard duplex one pass
<b>Original Size</b>	5.5" x 8.5" - 11" x 17"
<b>Original Weight</b>	11 - 34 lb. Simplex/14 - 34 lb. Duplex
<b>Copying Speed</b>	60/75 OPM
<b>Original Table Capacity</b>	100 sheets
<b>Original Set</b>	Face Up
<b>Original Feed</b>	Automatic Feed

## OPTIONAL ACCESSORIES

<b>Large Capacity Tray (RT43)</b>	
<b>Paper Size</b>	8.5" x 11"
<b>Paper Capacity</b>	4,000 sheets
<b>Paper Weight</b>	14 - 34 lb.
<b>Dimensions (WxDxH)</b>	12.4" x 18.1" x 25.9"
<b>Weight</b>	44 lbs.

## PRINTER DIMM SPECIFICATIONS

<b>Print Speed</b>	60/75 PPM
<b>CPU</b>	RM7000A - 375 MHz
<b>Interface</b>	Standard - Parallel IEEE1284, Ethernet NIC Optional - IEEE1394, Wireless LAN, USB 2.0
<b>Network Protocol</b>	TCP/IP, IPX/SPX, NetBEUI, AppleTalk
<b>Memory Capacity</b>	Required 256 MB (up to 384 MB)
<b>Printer Hard Disk Drive</b>	40 GB (Shared with Copier)
<b>Language</b>	RPCS, PCL5e/PCL6 (Standard) Adobe PostScript 3 (Optional)
<b>Print Resolution</b>	Up to 1200 dpi
<b>Drivers for PCL 6</b>	Windows 95/98, Me, NT4.0, Windows 2000, XP
<b>Drivers for PS3</b>	Windows 95/98, Me, NT4.0, Windows 2000, XP, Macintosh, UNIX
<b>Utility</b>	SmartNetMonitor

## PRINTER/SCANNER DIMM SPECIFICATIONS

<b>Same as Printer DIMM Specifications plus the following:</b>	
<b>Scan Speed</b>	75 SPM
<b>Image Resolution</b>	100 - 600 dpi
<b>File Format</b>	PDF, TIFF, JPEG
<b>Destination</b>	Scan-to-File, Scan-to-Intray, Scan-to-Email
<b>Scan Protocol</b>	TCP/IP

## FINISHER (SR840)

<b>Type</b>	Floor Standing
<b>Shift Tray</b>	
<b>Stack Capacity</b>	3,000 sheets (8.5" x 11", 20 lb. Bond) w/o Punch 1,500 sheets (8.5" x 14" & larger, 20 lb. Bond) w/o Punch 14 lb. Bond - 110 lb. Index
<b>Paper Weight</b>	100 sheets (8.5" x 11" & smaller, 20 lb. Bond)
<b>Staple Capacity</b>	50 sheets (8.5" x 14" & larger, 20 lb. Bond)
<b>Staple Paper Size</b>	8.5" x 11", 8.5" x 14", 11" x 17"
<b>Staple Positions</b>	Top, Bottom, Two Staples, Top Slant
<b>Hole Punch</b>	Optional 2 and 3 hole (user selectable)
<b>Proof Tray</b>	
<b>Paper Sizes</b>	5.5" x 8.5" - 11" x 17"
<b>Paper Weight</b>	14 lb. Bond - 110 lb. Index
<b>Stack Capacity</b>	500 sheets (8.5" x 11" & smaller, 20 lb. Bond) 250 sheets (8.5" x 14" & larger, 20 lb. Bond)

## FINISHER (SR850)

<b>Type</b>	Floor Standing
<b>Shift Tray</b>	
<b>Stack Capacity</b>	3,000 sheets (8.5" x 11", 20 lb. Bond) w/o Punch 1,500 sheets (8.5" x 14" & larger, 20 lb. Bond) w/o Punch 14 lb. Bond - 110 lb. Index
<b>Paper Weight</b>	50 sheets (8.5" x 11" & smaller, 20 lb. Bond) with Punch
<b>Staple Capacity</b>	30 sheets (8.5" x 14" & larger, 20 lb. Bond) with Punch 30 sheets (8.5" x 11" & smaller, 20 lb. Bond) w/o Punch 30 sheets (mixed paper size)
<b>Staple Paper Size</b>	8.5" x 11", 8.5" x 14", 11" x 17"
<b>Staple Positions</b>	Top, Bottom, Two Staples, Top Slant
<b>Hole Punch</b>	Optional 2 and 3 hole (user selectable)
<b>Proof Tray</b>	
<b>Paper Sizes</b>	5.5" x 8.5" - 11" x 17"
<b>Paper Weight</b>	14 lb. Bond - 90 lb. Index
<b>Stack Capacity</b>	250 sheets (8.5" x 11" & smaller, 20 lb. Bond) w/o Punch 50 sheets (8.5" x 14" & larger, 20 lb. Bond) w/o Punch

## FINISHER (SR860) WITH SADDLE STITCH

<b>Type</b>	Floor Standing
<b>Shift Tray</b>	
<b>Stack Capacity</b>	2,500 sheets (5.5" x 8.5" - 8.5" x 11", 20 lb. Bond) 1,250 sheets (8.5" x 14" & larger, 20 lb. Bond)
<b>Paper Weight</b>	14 - 40 lb. Bond, 110 lb. Index
<b>Staple Capacity</b>	50 sheets (8.5" x 11" & smaller) 30 sheets (8.5" x 14" & larger) 30 sheets (mixed paper sizes)
<b>Staple Paper Size</b>	8.5" x 11", 8.5" x 14", 11" x 17"
<b>Staple Positions</b>	Top, Center, Two Staples
<b>Hole Punch</b>	Optional 2 and 3 hole (user selectable)
<b>Proof Tray</b>	
<b>Paper Sizes</b>	5.5" x 8.5" - 11" x 17"
<b>Paper Weight</b>	14 - 40 lb. Bond, 90 lb. Index
<b>Stack Capacity</b>	250 sheets (5.5" x 8.5" - 8.5" x 11") 50 sheets (8.5" x 14" & larger)
<b>Saddle Stitch Function</b>	
<b>Maximum Paper Size</b>	8.5" x 11" and 11" x 17"
<b>Paper Weight</b>	17 - 28 lb. Bond (1 cover at 14 - 34 lb. Bond)
<b>Staple Capacity</b>	15 sheets
<b>Folding</b>	Center Folding

## OTHER OPTIONS

Copy Tray 1075	8.5" x 14" Tray Type 1075
9-Bin Mailbox CS 390	Cover Interposer Tray Type 1075
Tab Sheet Holder Type 1075	Connect Copy

**savin**



Savin Corporation Stamford, Connecticut 06904 ©2002 Savin Corporation. SAVIN® is a registered trademark of Savin Corporation. All other trademarks are the property of their respective owners. Product specifications subject to change without notice. Printed in U.S.A. (S1711) 100M 6/02

Our earth,  
Our tomorrow