



imageRUNNER 7200 Specifications

Type: Digital, Multifunction Imaging System
Imaging System: Laser Dry Electrostatic Transfer
Developing System: Dry Monocomponent Toner Projection
Image Server Memory: Standard 192MB RAM + 10GB HDD
First-copy Time: 3.1 Seconds from Platen Glass
 4.3 Seconds from ADF
Warm-up Time: 6 Minutes or Less
Acceptable Originals: Sheets, Books, 3-dimensional Items
Max. Original Size: 11" x 17" (Ledger)
Max. Copy Size: 11" x 17" (Ledger)
Min. Copy Size: 4-1/8" x 5-7/8"
Max. Copy Reservation: 5 Jobs
Copy/Scanning Resolution: 600 dpi x 600 dpi
 1200 dpi x 600 dpi Interpolated
 600 dpi x 600 dpi
Printing Resolution: 2400 dpi x 600 dpi Interpolated
 256 Gradations of Gray
Halftone: 72 cpm (Letter)
Copy Speed: 36 cpm (Ledger)
Duplexing: Standard Automatic Trayless
Magnification Reduction/Enlargement: 25% to 400% in 1% Increments
Paper Supply Standard: Dual Front-loading Trays (1,500 Sheets Each)
 Dual Front-loading Cassettes (50 Sheets Each)
 50-sheet Stack Bypass
 3,500-sheet Paper Deck-M1 (Total: 7,650 Sheets)
Optional: Multiple Copies: 1 to 9,999
 Paper Weights: 17 lb. Bond to 110 lb. Index (All Paper Sources)
 Mail Box: 100 (7,700 Pages/Letter)
 Dept. ID: 1,000 (7-digit IDs and Passwords)

Supplies
Drum: Amorphous Silicon – Estimated Yield: 5,000,000 Impressions
Maximum Duty Cycle: 350,000 Impressions per Month
Toner: Magnetic Positive Toner – Estimated Yield: 33,000 Images

ACCESSORIES

Automatic Document Feeder
 Acceptable Originals: Statement to Ledger
 Scanning Speed: 55 ppm (Letter)
 Capacity: 100 Sheets (All Sizes/20 lb.)
 Paper Weights: 13 lb. Bond to 32 lb. Index

Finisher-K1N/K2N (Optional)
 Number of Trays: 2 Trays
 Tray Capacity: 1,000 Sheets (All Sizes)
 Top Tray: Offset Stacking

Lower Tray: 2,000 Sheets (Letter)
 1,000 Sheets (11" x 17", Legal)
 Offset Stacking
Staple Position: 1 - Any Corner
 2 - Side Margin
Max. Stapling Capacity: 100 Sheets (Letter/Statement)
 50 Sheets (Letter-R/Legal/11" x 17")
Hole-punch (K2N Only): 3 Holes (11" x 17", Letter)
 2 Holes (Legal, Letter-R)

Saddle Finisher-K3N (Optional)
 Number of Trays: 3 Trays
 Tray Capacity: 1,000 Sheets (All Sizes)
 Top Tray: Offset Stacking
 Lower Tray: 1,000 Sheets (11" x 17", Legal)
 Offset Stacking
Saddle-stitch Tray: 30 Sets
Staple Position: 1 - Any Corner
 2 - Side Margin
Max. Stapling Capacity: 100 Sheets (Letter/Statement)
 50 Sheets (Letter-R/Legal/11" x 17")
Hole-punch: 3 Holes (11" x 17", Letter)
 2 Holes (Legal, Letter-R)

Saddle-stitch Capabilities
Saddle-stitch Paper Sizes: 11" x 17", Letter
Stapling Capacity: 15 Sheets (60 Pages)
Folding: V-folding Standard
Paper Deck-M1 (Optional)
Paper Capacity: 3,500 Sheets
Paper Size: Letter
Paper Weights: 17 lb. Bond to 110 lb. Index

Document Insertion Unit-B1 (Optional)
 Paper Sizes: Letter-R to 11" x 17"
 Paper Weights: 17 lb. Bond to 110 lb. Index
 Feeder Capacity: Letter, Letter-R: 100 Sheets
 Legal, 11" x 17": 50 Sheets

Paper Folding Unit-C1 (Optional)
 Paper Sizes: 11" x 17" Only
 Paper Weights: 17 lb. Bond to 22 lb. Bond
 Fold Type: Z-fold

Booklet Trimmer-A1 (Optional)
 Sheet Capacity: 30 Sheets (60 Pages)
 Stack Capacity: 2,000 Pages
 Dust Capacity: 2,000 Pages

Network Multi-PDL Printer Kit-B3 (Optional)
PDL Support: PostScript 3 Emulation
 PCL 5e, PCL 6
Interface Connections: RJ-45 (10/100Base-T)
 IEEE 1284
 Token Ring (Optional Card)
Protocol Stacks: Ethernet
 IPX/SPX™: 802.2, 802.3
 Ethernet II, 802.2 SNAP
 TCP/IP
Network OS: AppleTalk® Phase II
 Novell® NetWare v3.2, 4.1, 4.11, 4.2, 5, 5.1
 Windows® 95/98/Me
 Windows NT® 4.0/2000/XP
 Solaris™ 1.x, 2.5 or Later*
 Apple® System 7.5 or Higher
 NDPS, Port 9100, IPP
Print Service: Network ScanGear, Remote UI,
 NetSpot, Universal Send

Canon imagePASS-M1 Print Controller (Optional)
Hardware: External Stand-alone Controller
Processor: Intel Mobile Pentium III 500MHz
Memory: 128MB DIMM
Storage: 10.2GB Hard Disk Drive
PDL Support: Adobe PostScript 3
 PCL 5e, PCL 6, P/L
 RJ-45 (10/100Base-T)
Interface Connections: IEEE 1284
 Token Ring (Optional Card)
 Ethernet
 IPX/SPX: 802.2, 802.3
 Ethernet II, 802.2 SNAP
 TCP/IP
Network OS: AppleTalk: 802.2 SNAP and AppleTalk Phase II
 Novell NetWare v3.2, 4.1, 4.11, 4.2, 5, 5.1
 Windows 95/98/Me
 Windows NT 4.0/2000/XP
 Solaris 1.x, 2.5 or Later*
 Apple System 8.6 or Higher
 NDPS, Port 9100, IPP
Print Service: Network ScanGear, Remote UI, Universal Send,
 NetSpot (except Job Monitor)
Additional Functions Standard: Command WorkStation, Fiery Downloader,™
 Fiery Link,™ WebTools

Send Expansion-A1 SET (for Universal Send Support)
Sending Method: E-mail, I-fax, Database (Salutation), File Server
 (IPX, FTP, SMB)
Address Book Capacity: Maximum 1,800
File Format: TIFF, PDF, MTIFF
Sending Size: Statement to Ledger
Scan Density: 200 dpi, 300 dpi, 400 dpi, 600 dpi

Dimensions Table	Dimensions (H x W x D)	Weight	Power
imageRUNNER 7200 Main Unit	46-1/8" x 30-1/8" x 31-3/8" (1171mm x 764mm x 795mm)	602 lb. (273kg)	208V, 60Hz, 12A
Finisher-K1N	39-1/4" x 26-1/4" x 29-1/8" (995mm x 667mm x 738mm)	141 lb. (64kg)	Directly from Main Unit
Finisher-K2N	39-1/4" x 26-1/4" x 29-1/8" (995mm x 667mm x 738mm)	145 lb. (66kg)	Directly from Main Unit
Saddle Finisher-K3N	39-1/4" x 31-5/8" x 29-1/8" (995mm x 803mm x 738mm)	280 lb. (127kg)	Directly from Main Unit
Paper Deck-M1	22-5/8" x 12-3/4" x 23" (574mm x 323mm x 583mm)	90.3 lb. (41kg)	Directly from Main Unit
Document Insertion Unit-B1	5-5/8" x 22-1/8" x 23" (144mm x 561mm x 584mm) (with Auxiliary Tray Opened)	35 lb. (16kg)	Directly from Main Unit
Paper Folding Unit-C1	39-1/4" x 7-1/4" x 26-5/8" (995mm x 184mm x 675mm)	108 lb. (49kg)	Directly from Main Unit
Booklet Trimmer-A1	22" x 44" x 24" (560mm x 1118mm x 610mm)	149 lb. (68kg)	120V, 3A
imagePASS-M1 Print Controller	14" x 6-3/8" x 11" (355mm x 162mm x 279mm)	11.6 lb. (5.3kg)	110-240V, 1A

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency, except when attached to the optional Token Ring Adapter on the Network Multi-PDL Printer Kit-B3 or the optional imagePASS-M1 Print Controller. The ENERGY STAR name is a registered trademark of the U.S. Environmental Protection Agency. Intel and Pentium are registered trademarks of Intel Corporation. Adobe and PostScript are registered trademarks of Adobe Systems Incorporated. Apple is a trademark of Apple Computer, Inc., registered in the U.S. and other countries, and AppleTalk is a registered trademark of Apple Computer, Inc. Solaris is a trademark of Sun Microsystems, Inc. in the United States and other countries. Fiery is a registered trademark and EFI, WebTools, Fiery Downloader, Fiery Link, DocBuilder, Command WorkStation and FreeForm are trademarks of Electronics for Imaging, Inc. eCopy, ShareScan, and Desktop are trademarks of eCopy, Inc. Windows, Windows NT, PowerPoint, and Microsoft are registered trademarks of Microsoft Corporation in the United States and/or other countries. NetWare and Novell are registered trademarks, and IPX/SPX is a trademark of Novell, Inc. HP, PCL, and OpenView are registered trademarks of Hewlett-Packard Company. Tivoli is a registered trademark of Tivoli Systems Inc. in the United States, other countries, or both. Patrol is a registered trademark of BMC Software, Inc. Canon and NetSpot are registered trademarks and Canon Know How, IMAGERUNNER, and the GENUINE logo are trademarks of Canon Inc. IMAGEWARE, Universal Send and Remote UI are trademarks, and IMAGEANYWARE is a service mark of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged.

Specifications are subject to change without notice.

0027W662

0302-iR7200-100M



PRINTED ON RECYCLED PAPER IN THE U.S.A.



*Please check with your local Canon-authorized Dealer for availability.

▲The Document Insertion Unit-B1, the Paper Folding Unit-C1, and the Booklet Trimmer-A1 can only be used with the Saddle Finisher-K3N.

■The imageRUNNER 7200 is not ENERGY STAR® compliant when attached to the optional Token Ring Adapter on the Network Multi-PDL Printer Kit-B3 or the optional imagePASS-M1 Print Controller.



1-800-OK-CANON
 www.usa.canon.com

Canon U.S.A., Inc.
 One Canon Plaza
 Lake Success, NY 11042