

2900 Digital Reprographic System

January 2001

The KIP 2900 Digital Reprographic System is shown with optional controller stand



2900 Digital Copier

The 2 roll, KIP 2900 Digital Copier provides low volume copying at 3 "D" size/min. or 1.6 inches/sec. The copier includes 25-400% zoom, up to 99 copies in a single run from an original up to 36" x 20". The KIP 2900 may be upgraded at any time to a full Digital Reprographic System.

2900 Digital Reprographic System

The KIP 2900, when combined with the KIP **Powerprint Standard Controller**, provides a complete turnkey solution for low volume production 3 "D" size/min., copying, printing, scanning, viewing and storing of documents up to 36" by 50' long. Includes: Interface Cables, Windows NT workstation 4.0, Powerprint Software Suite including Powerprint Scan, Powerprint Request/Q-vue/Q-Manager, and Powerprint Unattend. The KIP 2900 Scanner functions at 1.6-6.4 inches/sec. scanning speed ranging from 100 to 400 dpi to create TIFF Group 4, CALS Group 4 formats. Installation instructions, operators manual included.

Printer Specifications:

Dimensions: 54" (W) x 21" (D) x 35" (H)
Weight: 440 lbs
Power requirements: 15 Amp, 120V
Power consumption: 1300W
Print delivery: Rear
Technology: Electrophotography (LED head) with Organic Photoconductor Drum and closed toner system

Scanner Specifications:

Dimensions: 54" (W) x 19" (D) x 10" (H)
Weight: 123 lbs
Power requirements: 100~240V
Power consumption: 100W
Method: Flat straight transport path with U-turn
Reading Sensor: Silicon-CCD
Light Source: LED Array

NOTE: All specifications subject to change without notice.

Product Overview

Product Specifications

Features:

- Prints at 3 "D" size/ min. or 1.6 inches /sec.
- Scans at 1.6 inches/sec. @ 400 DPI
- Scans at 3.8 inches/sec. @ 200 DPI
- Designed for low volume production

Accepted CAD Formats:

Auto recognition of HPGL 1/2, HP-RTL, and Calcomp 906/907

Accepted Raster Formats:

CCITT CALS Group 4, TIFF Group 4, PCX, Intergraph CIT/TG4, Versatec Color Graphics (VCGL), Uncompressed Color/ Grayscale TIF, TIFF Packbits, IBM IOCA, EDMICS, and TLC (KIP)

Optional- ATA compliant CGM, Postscript Levels 1/2, PDF (up to revision 1.2), Encapsulated Postscript Levels 1/2, and JPEG

Powerprint Standard Controller:

Celeron 533 MHz, 64 MB SDRAM, 7200 RPM 20.0+ GB Hard Drive, 10/100 PCI Network Card, AGP Video Board, 48 x CD-ROM, 3.5" floppy, and Windows NT 4.0.

Powerprint Controller KIT also available

Network Protocols:

TCP/IP, NetBEUI (smb), Novell (IPX/SPX), And LPR/LPD

Included Drivers:

KIP ADI Driver for AutoCAD 14
KIP HDI Drivers for AutoCAD 2000/2000i
KIP Windows Driver

Standard Hard Disk Storage:

20.0+ Gigabyte of Hard Drive storage with 4.0 Gigabyte used as workspace.

KIP America Phone: 800.252.6793 **Website:** www.kipamerica.com **Email:** sales@kipamerica.com

Contact your Local KIP America Authorized Dealer